DX2 – THE DESKTOP MIXER



100000

DHD-AUDIO.COM

2+-

THE DESKTOP MIXER

The new DX2 is a fully featured desktop audio mixing system designed for use wherever space is at a premium such as in video edit booths, news commentary suites, radio OB vans and professional podcast studios.

CONTROL INTERFACE

The DX2 offers the same simplified user experience as all the other DHD mixers but in the smallest possible size: a tabletop housing.

The central module (52-1214) has 4 faders and a monitoring and talkback section. All necessary I/Os are available directly from the central module. They comprise a broadcast-quality XLR microphone input, 6.3 mm jack, right and left line outputs to feed active loudspeakers, a 6.3 mm jack stereo headphone output and a 3.5 mm minijack I/O port allowing direct audio insertion from a smartphone.

IPx slot for Dante

and AES67 (option)

DHD Network, 16x16 ch AES67

(software option)

Each fader module (52-1220) has 6 professional-grade 100 mm motorised faders with dust-protection and can be configured to support a second layer.

Both modules incorporate a 7.8 inch multitouch screen for fader parameters and central control. The user interface on each touchscreen can be configured individually. Level meters for busses and all faders, call and on-air signalisation, a clock, and many more tools can be displayed. The maximum number of faders depends on the capabilities of the connected core.

wordclock, AES11, PAL, NTSC,

HD tri-level sync (option)

FEATURES

- Rock-solid tabletop units for 24/7 use
- 7.8" multitouch display (Unicode support)
- 100 mm motorised faders, dust-protected
- Two potentiometers for headphones and loudspeakers
- Illuminated main control encoder for haptic control of display encoders
- Built-in talkback mic and rear-panel I/O
- Ambient-light sensor
- powered GPOs for m!ka Arm LEDs

INTEGRATION

The DX2 can be connected to all XS3, XC3 and XD3 cores. It works with all current DHD I/O modules such as the Dante or AES67 AoIP interfaces, 3G/HD SDI embedders/de-embedders, MADI or DHD APC audio.

2x2 ch USB audio

DX2 4 FADER BUNDLE

52-1930

CONTROL UNIT WITH 4 MOTOR FADERS, 7.8" TOUCHSCREEN (52-1214)

19" RACK UNIT (1 U) XS3 CORE (52-7500) + Multi I/O Box (52-1340A)

48 V POWER SUPPLY (52-7498)

When ordering a bundle, you will benefit from an attractive package price and simplified DX2config software for easy setup.

A DX2 Bundle contains the complete hardware for a 4 fader mixing console with 2 layers for broadcast applications.

A DX2 Bundle with a 64 x 64 channel Dante interface is also available (52-1931).

52-1214



Specifications and design are subject to change without notice. The content of this document is for information only. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof neither conveys nor implies any license under patent rights or other industrial or intellectual property rights. All registered names and trade marks are the property of their respective owners. Version 2023-08-08